

PRODUCT DESCRIPTION

A Classical modified oil/hydrocarbon resin based long life, interior, exterior high shine aluminium coating for a wide range of substrates/objects that need a highly durable coating Aluminium finish

PRODUCT FEATURES

- Highly durable and UV resistant for the harsh South African climate
- Excellent adhesion to range of properly prepared substrates
- Excellent, no mess application properties, with excellent, flow and levelling
- Very versatile.

APPLICATION AREAS

- Primed metal and other substrates.

SURFACE PREPARATION

Rusted Metal: Affected areas need to be cleaned back to bright metal and spot primed with Heritage Red Oxide Metal primer.
New Metal: Surfaces need to be abrasively degreased (Heritage Galvanized Iron Cleaner) to remove the manufacturer's grease protective layer this process is repeated until the surface is water break free. After drying the whole substrate is coated with Heritage Red Oxide Metal primer.

Dry uncoated concrete surfaces: Remove all dust, foreign material, Fungal, algae growth- fill and seal all visible cracks and coat with Heritage Plaster Primer

Uncoated weathered or new fibre cement surfaces: Remove dust, foreign material, Fungal, Algae growth and if friable, powdery seal with Heritage Plaster Primer

Raw Plaster: Remove all dust, foreign material, Fungal and Algae growth. Fill all visible cracks and coat with Heritage Plaster Primer

Previously Painted Surfaces: Remove all loose, flaking and bubbling paint. Remove all dust, grease, foreign material, Fungus and Algae growth. Allow to dry, if then powdery or friable seal with Heritage Plaster Primer.

APPLICATION PROCEDURE

- Stir well before use
- Brush apply a generous coat of Chrome Aluminium to the area, which needs protecting
- Allow to dry 18-24hours before recoating
- Brush, roller or airless spray apply a second generous coat
- Clean up application equipment with Mineral turpentine/white sprits or Heritage Brush Cleaner Degreaser

GENERAL

- Do not apply before 9am and after 4 pm in the Winter
 - Do not apply exterior if it looks like rain will occur with in 4-6 hours of application
 - This Product is ready for use un-thinned, thinning will reduce its hiding power
 - 2 coats of Heritage Chrome Aluminium are used for best results
 - Although the spreading rate will vary with porosity and type of substrate
- For uncoated new work on 8-10 SQM/l for the first coat and 10-12 SQM/l for subsequent coats and for when applied to sealed, previously painted substrates
- Application equipment clean up is with Mineral turpentine/White Sprits, Heritage Brush Cleaner/Degreaser

COLOUR RANGE/QUANTITIES

- Chrome Aluminium only
- Available in 1/5/20 litres

PRECAUTIONS

- This material is highly flammable and has a flashpoint of 37 deg C
- Only apply in ventilated areas, keep away from all ignition sources, flames and sparks. Do not eat drink or smoke while applying.



LEAVE A LASTING IMPRESSION



info@heritagepaints.co.za

www.heritagepaints.co.za | 0800 0 PAINT - 0800 0 72468

Heritage Paints C.C. 18 Garland Street, Ophirton, Johannesburg