

PRODUCT DESCRIPTION

A classical alkyd based school board paint, which has been especially formulated to give the best long term performance for the end use of repainting worn out chalk boards.

PRODUCT FEATURES

- A quick drying and slightly coarse coating suitable for clear and visible writing when chalk is used
- Excellent adhesion, hiding power
- Excellent, no mess application properties
- Can be cleaned with normal house hold cleaners on a regular basis

APPLICATION AREAS

- Hardboard and Fibre cement boards
- Primed metal and wooden substrates

SURFACE PREPARATION

- Rusted Metal:** Affected areas need to be cleaned back to bright metal and spot primed with Heritage Water Based Metal Primer.
- New Metal:** Surfaces need to be abrasively degreased to remove the manufacturer's grease protective layer this process is repeated until the surface is water break free. After drying the whole substrate is coated with Heritage Water Based Metal Primer
- Uncoated dry concrete surfaces:** Remove all dust, foreign material, Fungal, algae growth- fill and seal all visible cracks and where repaired seal with Heritage Bonding Liquid and then prime with Heritage Plaster Primer
- Uncoated weathered or new fibre cement surfaces:** Remove dust, foreign material, Fungal, Algae growth and if friable, powdery seal with Heritage Bonding liquid, prime with Heritage Plaster primer
- Raw Plaster:** Remove all dust, foreign material, Fungal and Algae growth. Fill and seal all visible cracks and prime with Heritage Plaster primer
- Previously Painted Surfaces:** Remove all loose, flaking and bubbling paint. Remove all dust, foreign material, Fungus and Algae growth. Allow to dry, If then powdery or friable seal with Heritage Bonding Liquid and prime with Heritage Plaster Primer
- Uncoated wood:** Sand until smooth, Apply one coat of Heritage Universal Undercoat.

APPLICATION PROCEDURE

- Brush, roller or spray apply a generous coat of Heritage School Board Enamel to the area, which needs protecting
- Allow to dry overnight before recoating

GENERAL

- Do not apply before 9am and after 4 pm in the Winter
- Heritage School Board Enamel is ready for use un-thinned , thinning will reduce its hiding power
- Although the spreading rate will vary with porosity and type of substrate. For uncoated new work on 7-9 SQM/l for the first coat and 9-11 SQM/L for subsequent coats and for when applied to sealed, previously painted substrates
- Application equipment clean up is with white Spirits/Mineral Turpentine or Heritage Brush Cleaner Degreaser

COLOUR RANGE/QUANTITIES

- Green /Black
- 1/5/ 20 litres

PRECAUTIONS

- This product contains no toxic substances but is flammable
- It should only be used in well ventilated areas and you should not eat, drink or smoke, whilst using it.



LEAVE A LASTING IMPRESSION



info@heritagepaints.co.za

www.heritagepaints.co.za | 0800 0 PAINT - 0800 0 72468

Heritage Paints C.C.18 Garland Street, Ophirton, Johannesburg