

PRODUCT DESCRIPTION

A Classical silicone Modified alkyd based Hammertone effect coating for items (e.g. Filing Cabinets) that need a hard and highly washable/scratch resistant coating

PRODUCT FEATURES

- Highly washable, cleanable, humidity and scratch resistant
- Excellent adhesion to range of properly prepared substrates
- Excellent, no mess application properties, with excellent, flow and levelling
- High hiding power and film build.

APPLICATION AREAS

- Primed metal
- Previously painted substrates

SURFACE PREPARATION

Rusted Metal: Effectuated areas need to be cleaned back to bright metal and spot primed with QD or Etch Primer.

New Metal: Surfaces need to be abrasively degreased to remove the manufacturer's grease protective layer this process is repeated until the surface is water break free. After drying the whole substrate is coated with Quick Dry or Etch Primer

Previously Painted Surfaces: Remove all loose, flaking and bubbling paint. Remove all dust, grease, foreign material, Fungus. Allow to dry.

APPLICATION PROCEDURE

- Stir well before use
- Airless spray (thin for spray to 20-25 seconds Ford 4 cup with Heritage Q.D.E, Lacquer Thinner) apply a generous coat of Heritage Hammertone. to the area, which needs protecting
- Allow to dry 1-2 hours before recoating
- Airless spray apply a second generous coat
- Clean up application equipment with Heritage QDE or Lacquer thinner.

GENERAL

- Do not apply before 9am and after 4 pm in the Winter
 - Do not apply exterior if it looks like rain will occur with in 4-6 hours of application
 - 2-3 coats of Heritage Hammertone are used for best results
 - Although the spreading rate will vary with porosity and type of substrate
- For uncoated new work on 7-9 SQM/l for the first coat and 10-12 SQM/l for subsequent coats and for when applied to sealed, previously painted substrates
- Application equipment clean up is with Heritage Q.D.E. or Lacquer thinners

COLOUR RANGE/QUANTITIES

- Heritage Hammertone. is available in a limited colour range
- Available in 1/5/20 litres

PRECAUTIONS

- This material is highly flammable
- Only apply in ventilated areas, keep away from all ignition sources, flames and sparks. Do not eat drink or smoke while applying.



LEAVE A LASTING IMPRESSION



info@heritagepaints.co.za

www.heritagepaints.co.za | 0800 0 PAINT - 0800 0 72468

Heritage Paints C.C. 18 Garland Street, Ophirton, Johannesburg