

PRODUCT DESCRIPTION

A classical Bitumen based long life, interior, exterior high shine Aluminium coating for a wide range of substrate/objects that need a highly durable and humidity but cost effective aluminium finish.

PRODUCT FEATURES

- Highly durable, humidity and UV resistant for the harsh South African climate
- Excellent adhesion to range of properly prepared substrates
- Excellent, no mess application properties, with excellent, flow and levelling that gives a really even finish
- Very cost effective.

APPLICATION AREAS

- Primed metal and other substrates/roofs, especially in humid areas

SURFACE PREPARATION

Rusted Metal: Affected areas need to be cleaned/sand blasted back to bright metal and spot primed with Heritage Water Based Metal Primer

New Metal: Surfaces need to be abrasively degreased to remove the manufacturer's grease protective layer this process is repeated until the surface is water break free. After drying the whole substrate is coated with Heritage Water Based Metal Primer

Primed metal or previously coated surfaces: (with Aluminium) – check adhesion. Remove all peeling and flaking Paint. Clean/degrease preferably with a high pressure cleaner. Bare metal areas need to spot primed.

Fibre cement and roofing felt: Remove any flaking/peeling loose paint, wash off dust/mica particles with a hose pipe/hard broom, carry out repairs if required, allow to dry.

APPLICATION PROCEDURE

- Stir well before use
- Brush, Mohair roller apply a generous coat of Heritage Bituminous Aluminium to the area, which needs protecting
- Allow to dry 4-6 hours before recoating
- Brush, roller or airless spray apply a second generous coat
- Clean up application equipment with Xylene or Heritage Brush Cleaner Degreaser

GENERAL

- Do not apply before 9am and after 4 pm in the Winter
- Do not apply exterior if it looks like rain will occur within 4-6 hours of application
- This Product is ready for use un-thinned, thinning will reduce its hiding power
- Two coats of this Product are used for best results
- Although the spreading rate will vary with porosity and type of substrate. For uncoated new work on 8-10 SQM/l for the first coat and 10-12 SQM/l for subsequent coats and for when applied to sealed, previously painted substrates
- Application equipment clean up is with Heritage Brush Cleaner/Degreaser

COLOUR RANGE/QUANTITIES

- Shiny Aluminium only
- Available in 1/5/20 litres

PRECAUTIONS

- This material is highly flammable and has a flashpoint of 37 deg C
- Only apply in ventilated areas, keep away from all ignition sources, Flames and sparks. Do not eat drink or smoke while applying.
- Do not coat the inside of containers or water storage tanks with this product



LEAVE A LASTING IMPRESSION



info@heritagepaints.co.za

www.heritagepaints.co.za | 0800 0 PAINT - 0800 0 72468

Heritage Paints C.C. 18 Garland Street, Ophirton, Johannesburg