

PRODUCT DESCRIPTION

A classical Bitumen based long life, high water resistant black coating for a wide range of substrate/objects that need a highly water and humidity but cost effective finish.

PRODUCT FEATURES

- High humidity resistant for the Harsh Namibian climate
- Excellent adhesion to range of properly prepared substrates
- Excellent, no mess application properties, with excellent, flow and levelling that gives a really even finish.
- Very cost effective

APPLICATION AREAS

- Primed metal and other substrates/roofs, especially in humid areas
- Building foundations and retaining walls as a cost effective water proofing material

SURFACE PREPARATION

Rusted Metal: Affected areas need to be cleaned/sand blasted back to bright metal and spot primed with Heritage Water Based Red Oxide Metal primer.

New Metal: Surfaces need to be abrasively degreased to remove the manufacturer's grease protective layer this process is repeated until the surface is water break free. After drying the whole substrate is coated with Heritage Water Based Red Oxide metal primer

Primed metal or previously coated surfaces: Check adhesion - Remove all peeling and Flaking Paint. Clean/degrease preferably with a high pressure cleaner. Bare metal areas need to spot primed.

Fibre cement and roofing felt: Remove any flaking/peeling loose paint, wash off dust/mica particles with a hose pipe/hard broom, carry out repairs if required, allow to dry.

APPLICATION PROCEDURE

- Stir well before use
- Brush, Mohair roller apply a generous coat of Heritage Bituminous Black Paste to the area, which needs protecting
- Allow to dry 4-6 hours before recoating
- Brush, roller or airless spray apply a second generous coat
- Clean up application equipment with Mineral Turpentine, White Sprits or Heritage Brush Cleaner Degreaser

GENERAL

- Do not apply before 9am and after 4 pm in the Winter
- This Product is ready for use un-thinned, thinning will reduce its Effectiveness
- Two coats of this product are used for best results
- Although the spreading rate will vary with porosity and type of substrate. For uncoated new work on 5-7 SQM/l for the first coat and 6-8 SQM/l for subsequent coats and for when applied to sealed, previously painted substrates
- Application equipment clean up is with Mineral Turpentine/White Spirits or Heritage Brush Cleaner/Degreaser

COLOUR RANGE/QUANTITIES

- Black only
- Available in 1/5/20litres

PRECAUTIONS

- This material is highly flammable and has a flashpoint of 37 deg C
- Use only in well ventilated areas and do not eat, drink or smoke during application
- Only apply in ventilated areas, keep away from all ignition sources, flames and sparks. Do not eat drink or smoke while applying.



LEAVE A LASTING IMPRESSION



info@heritagepaints.co.za

www.heritagepaints.co.za | 0800 0 PAINT - 0800 0 72468

Heritage Paints C.C. 18 Garland Street, Ophirton, Johannesburg