

PRODUCT DESCRIPTION

A classical alkyd based Exterior water and weather resistant coating for exterior window/door/door frames for brush/spray application.

PRODUCT FEATURES

- Weather Resistant
- Excellent adhesion to properly prepared wooden substrates
- Excellent, no mess application properties, with excellent, flow and levelling

APPLICATION AREAS

- Properly prepared wooden/timber substrates.

SURFACE PREPARATION

- Sand the wooden substrate well, remove all dust.
- If the previously varnished area is sound (no sign of flaking peeling cracking etc) then sand well, but if the varnish shows signs of cracking etc, remove back to bare wood.

APPLICATION PROCEDURE

- Stir well before use.
- Brush apply the first coat diluted 10% with White Spirits/Mineral turpentine.
- Allow to dry 16-18 hours before sanding, again remove all dust.
- Brush/Spray apply two more generous coats leaving 16-18 hours between coats.
- Clean up application equipment with White Spirits/Mineral Turpentine/ Heritage Brush cleaner degreaser

GENERAL

- Do not apply before 9am and after 4 pm in the Winter.
- Three coats of Heritage Exterior Varnish are used for best results.
- Although the spreading rate will vary with porosity and type of substrate. For uncoated new work on 6-8 SQM/l for the first coat and 10-12 SQM/l for subsequent coats and for when applied to sealed substrates.
- Application equipment clean up is with White Spirits/Mineral Turpentine, Heritage Brush cleaner degreaser.

COLOUR RANGE/QUANTITIES

- This product is available in clear only
- Available in 1/5/20litres

PRECAUTIONS

- This material is highly flammable.
- Only apply in ventilated areas, keep away from all ignition sources, flames and sparks. Do not eat drink or smoke while applying.



LEAVE A LASTING IMPRESSION



info@heritagepaints.co.za

www.heritagepaints.co.za | 0800 0 PAINT - 0800 0 72468

Heritage Paints C.C.18 Garland Street, Ophirton, Johannesburg