



HERITAGE® P A I N T S

TECHNICAL DATA SHEET WOOD COATING INTERIOR WOOD SEALER

PRODUCT DESCRIPTION

A Classical alkyd based low solids coating for interior window/door/door frames for brush/spray application.

PRODUCT FEATURES

- Scratch resistant
- Excellent adhesion to properly prepared wooden substrates
- Excellent, no mess application properties, with excellent, flow and levelling

APPLICATION AREAS

- Properly prepared wooden/timber substrates.

SURFACE PREPARATION

- Sand the wooden substrate well, remove all dust.

APPLICATION PROCEDURE

- Stir well before use.
- Brush apply the first coat diluted 10% with White Sprits/Mineral turpentine.
- Allow to dry 16-18 hours before sanding, again remove all dust.
- Brush/Spray apply 1-2 more generous coats leaving 16-18 hours between coats.
- Clean up application equipment with White Spirits/Mineral Turpentine/ Heritage Brush cleaner degreaser

GENERAL

- Do not apply before 9am and after 4 pm in the Winter.
- Three coats of Heritage Exterior Varnish are used for best results.
- Although the spreading rate will vary with porosity and type of substrate. For uncoated new work on 6-8 SQM/l for the first coat and 10-12 SQM/l for subsequent coats and for when applied to sealed substrates.
- Application equipment clean up is with White Spirits/Mineral Turpentine, Heritage Brush cleaner degreaser.

COLOUR RANGE/QUANTITIES

- This product is available in clear only
- Available in 1/5/20litres

PRECAUTIONS

- This material is highly flammable.
- Only apply in ventilated areas, keep away from all ignition sources, flames and sparks. Do not eat drink or smoke while applying.



LEAVE A LASTING IMPRESSION



info@heritagepaints.co.za

www.heritagepaints.co.za | 0800 0 PAINT - 0800 0 72468

Heritage Paints C.C. 18 Garland Street, Ophirton, Johannesburg