

PRODUCT DESCRIPTION

A new generation Polyurethane/Alkyd based interior gloss floor coating for those high traffic areas that need a highly washable, alkali and abrasion resistant coating in a range of colours.

PRODUCT FEATURES

- Highly washable, cleanable, humidity and abrasion resistant
- Excellent adhesion to range of properly prepared, dry flooring substrates
- Excellent, no mess application properties, with excellent, flow and levelling
- High hiding power and film build
- Alkali resistant when applied to dry cement floors (moisture level 15% max)

APPLICATION AREAS

- Dry (moisture level 15% Max) cement floors

SURFACE PREPARATION

Dry (15% moisture Max) uncoated concrete surfaces: Remove all dust, foreign material, Fungal, algae growth- fill and seal all visible cracks with a suitable flexible sealant

Previously Painted Surfaces: Remove all loose, flaking and bubbling paint. Remove all dust, grease, foreign material, Fungus and Algae growth. Allow to dry-spot prime with Heritage Stoep Paint thinned 5% with White spirits/Mineral Turpentine

APPLICATION PROCEDURE

- Stir well before use
- Brush, Mohair roller apply a generous coat of Heritage Industrial Floor Coating to the area, which needs protecting
- Allow to dry 18-24hours before recoating
- Brush, roller a second generous coat
- Only apply in ventilated areas, keep away from all ignition sources, flames and sparks. Do not eat drink or smoke while applying.
- Industrial Floor Coating
- Clean up application equipment with White Spirit/Mineral Turpentine Brush cleaner degreaser.

GENERAL

- Do not apply before 9am and after 4 pm in the Winter
- 2 coats of this product are used for best results
- Although the spreading rate will vary with porosity and type of substrate. For uncoated new work on 6-8 SQM/l for the first coat and 8-10 SQM/l for subsequent coats and for when applied to sealed, previously painted substrates
- Application equipment clean up is with White Spirits/Mineral Turpentine or Brush Cleaner Degreaser

COLOUR RANGE/QUANTITIES

- This product is available in a range of Standard colours
- Available in 1/5/20litres

PRECAUTIONS

- This material is highly flammable and has a flashpoint of 37 deg C
- Use only in well ventilated areas and do not eat, drink or smoke during application



LEAVE A LASTING IMPRESSION



info@heritagepaints.co.za

www.heritagepaints.co.za | 0800 0 PAINT - 0800 0 72468

Heritage Paints C.C. 18 Garland Street, Ophirton, Johannesburg