

# SOLVENT BASED MASONRY PRIMER

## PRODUCT DESCRIPTION

Heritage Masonry Primer is a classical solvent/solution Acrylic based penetrating, bonding and stabilising liquid/sealer for interior and exterior use on powdery, friable and very porous or stained substrates such as old paint, new friable or porous plaster and fillers. Once the Heritage Masonry Primer has done its job these Areas can be over coated with a range of Heritage water and solvent based decorative products.

# **PRODUCT FEATURES**

- Excellent penetrating and binding properties
- Excellent adhesion
- Excellent alkali resistant properties
- Excellent stain blocking properties
- · Once sealed can be top coated with a wide range of Heritage Water and solvent based products

#### APPLICATION AREAS

- Powdery, friable weathered, previously painted areas
- Fire or nicotine stained areas.

#### SURFACE PREPARATION

**Previously Painted Surfaces:** Remove all loose, flaking and bubbling paint. Remove all dust, foreign material, Fungus and Algae growth. Allow to dry,

Lime wash coated walls: Remove lime wash as far as possible with scraper blades and or soft wire or hard fibre brushes but be careful not to damage the plaster. Dry Interior filler, sand carefully and remove dust. Dry Exterior cement based filler, sand carefully and remove dust

## **APPLICATION PROCEDURE**

- Apply Masonry Primer with brush or roller
- When dry (overnight) repeat the procedure if required
- Allow to dry before over coating with the required Heritage Primer/topcoat

# **GENERAL**

- Do not apply before 9am and after 4 pm in the Winter
- Do not apply exterior if it looks like rain will occur with in 4-6 hours of application
- Application equipment clean up is with White spirits/Mineral Turpentine, or Heritage Brush cleaner degreaser

# **COLOUR RANGE/QUANTITIES**

- White only
- 1/5/20 litres

## **PRECAUTIONS**

- This product continues no toxic substances but is flammable
- Only use in well ventilated areas, do not eat drink or smoke, whilst using

