



# HERITAGE® P A I N T S

## TECHNICAL DATA SHEET SOLVENT BASED UNIVERSAL UNDERCOAT

### PRODUCT DESCRIPTION

A classical alkyd based general purpose undercoat, which has been especially formulated to give the best long term performance for the total system. When used to provide a very strong and stable base for over coating with a wide range of Heritage water and solvent based products.

### PRODUCT FEATURES

- A quick drying and very smooth undercoat, just what you need as an undercoat for the harsh conditions found in South Africa.
- Excellent adhesion, Hiding power
- Excellent, no mess application properties
- Can be top coated with a wide range of Heritage Water and Solvent Based products

### APPLICATION AREAS

- Plaster, Hardboard and Fibre cement walls
- Primed metal and wooden substrates

### SURFACE PREPARATION

- Rusted Metal:** Affected areas need to be cleaned back to bright metal and spot primed with Heritage Water Based Metal primer.
- New Metal:** Surfaces need to be abrasively degreased (With Heritage Galvanized Iron Cleaner) to remove the manufacturer's grease protective layer this process is repeated until the surface is water break free.
- Uncoated dry concrete surfaces:** Remove all dust, foreign material, Fungal, algae growth. Fill and seal all visible cracks and where repaired seal with Heritage Bonding Liquid and then primed with Heritage Plaster or Masonry Primer
- Uncoated weathered or new fibre cement surfaces:** Remove dust, foreign material, Fungal, Algae growth and if friable, powdery seal with Heritage Bonding Liquid, prime with Heritage Plaster or Masonry Primer.
- Raw Plaster:** Remove all dust, foreign material, Fungal and Algae growth. Fill and seal all visible cracks and prime with Heritage Plaster or Masonry Primer.
- Previously Painted Surfaces:** Remove all loose, flaking and bubbling paint. Remove all dust, foreign material, Fungus and Algae growth. Allow to dry, If then powdery or friable seal with Heritage Bonding Liquid and prime with Heritage Plaster or Masonry Primer.

### APPLICATION PROCEDURE

- Brush, roller apply a generous coat of Heritage **Universal Undercoat** to the area, which needs protecting.
- Allow to dry overnight before recoating.

### GENERAL

- Do not apply before 9am and after 4 pm in the Winter
  - Do not apply exterior if it looks like rain will occur with in 4-6 hours of application
  - Heritage GP Undercoat is ready for use un-thinned , thinning with Mineral Turpentine/White Sprits will reduce its hiding power
  - Although the spreading rate will vary with porosity and type of substrate
- For uncoated new work on 7-9 SQM/l for the first coat and 9-11 SQM/L for subsequent coats and for when applied to sealed, previously painted substrates
- Application equipment clean up is with Mineral Turpentine/White Sprits

### COLOUR RANGE/QUANTITIES

- White only but other colours can be supplied in minimum batch quantities
- 1/5/20 litres

### PRECAUTIONS

- This product contains no toxic substances but is flammable with a flash point is 37 Deg C.
- It should only be used in well ventilated areas and you should not eat, drink or smoke, whilst using it . Its



LEAVE A LASTING IMPRESSION



info@heritagepaints.co.za

www.heritagepaints.co.za | 0800 0 PAINT - 0800 0 72468

Heritage Paints C.C. 18 Garland Street, Ophirton, Johannesburg