

PRODUCT DESCRIPTION

A Classical two pack epoxy based long life, interior, abrasion resistant gloss floor coating for those high traffic areas that need a highly abrasion water and chemical/acid resistant coating in a range of colours.

PRODUCT FEATURES

- Highly abrasion and chemical resistant
- Highly washable, cleanable
- Excellent adhesion to range of properly prepared substrates
- Excellent, no mess application properties, with excellent, flow and levelling
- High hiding power and film build

APPLICATION AREAS

- Dry Plaster/concrete substrates

SURFACE PREPARATION

Dry uncoated concrete surfaces: Remove all dust, foreign material, Fungal, algae growth. Fill and seal all visible cracks and coat with Heritage Epoxy Floor Coating.

Raw Plaster: Remove all dust, foreign material, Fungal and Algae growth.

Previously Epoxy painted Surfaces: Remove all loose, flaking and bubbling paint. Remove all dust, grease, foreign material, Fungus and Algae growth. Sand well to give the next coat of epoxy something to adhere to Allow to dry, after drying over night all primed areas and previously areas must then can be coated with Heritage Epoxy Floor Paint

APPLICATION PROCEDURE

- Stir well before use
- Mix the Epoxy base with the curing agent in the correct ratio: 4 Volumes Epoxy base to 1 volume curing agent, mix for 5–10 minutes
- Brush, Mohair roller or airless spray (thin for spray to 20-25 Sec Ford 4 with Xylene/Epoxy thinner) apply a generous coat of Epoxy Floor Coating to the area, which needs protecting
- Allow to dry 18-24hours but no longer than 48 hours before recoating
- Brush, roller or airless spray apply a second generous coat
- Clean up application equipment with Xylene/Epoxy thinners
- Only apply in ventilated areas, keep away from all ignition sources, flames and sparks. Do not eat drink or smoke while applying.

GENERAL

- Do not apply before 9am and after 4 pm in the Winter
 - 2 coats of the product are used for best results
 - Although the spreading rate will vary with porosity and type of substrate
- For uncoated new work on 6-8 SQM/l for the first coat and 10-12 SQM/l for subsequent coats and for when applied to sealed, previously Epoxy painted substrates
- Application equipment clean up is with Xylene/Epoxy Thinner

COLOUR RANGE/QUANTITIES

- Heritage Epoxy Floor paint is available in a limited range of popular ready mixed colours and in special colours in minimum batch quantities
- Available in 5 litres (2 pack containers)

PRECAUTIONS

- This material is highly flammable
- Use only in well ventilated areas and do not eat, drink or smoke during application
- Avoid skin contact by wearing Gloves/goggles if skin contact occurs, wash effected area with soap and water



LEAVE A LASTING IMPRESSION



info@heritagepaints.co.za

www.heritagepaints.co.za | 0800 0 PAINT - 0800 0 72468

Heritage Paints C.C. 18 Garland Street, Ophirton, Johannesburg