

PRODUCT DESCRIPTION

A classic, modified alkyd based, interior / exterior, low sheen roadmarking finish for unpainted bricks, cement, concrete, stone, bituminous and tarmac road surfaces to protect substrates from abrasion, rain and sun. Meets the rigorous requirements of SABS 731 Type 1.

APPLICATION AREAS

Bricks, cement, concrete, stone, bituminous and tarmac road surfaces on roads, airfields, parking areas and driveways. Bricks, cement, concrete, stone, bituminous and tarmac road surfaces on roads, airfields, parking areas and driveways.

PRODUCT FEATURES

- High abrasion resistance and durability.
- Excellent adhesion to a range of properly prepared road surface types.
- Heritage Paints Roadmarking contains highly reflective minerals for high visibility in parking and other areas.
- Meets SABS 731 Type 1 standards.
- Suitable for machine application as well as with a paint roller or brush.
- Serves as a base coating for the application of reflective glass beads.
- Available in the different shades required by municipalities and road authorities.

PRODUCT DATA

Resin Base Combination of synthetic resins

Drying Time Touch dry: 10-15 minutes

Hard dry: 1 - 2 hours

Solid Matter by Content By volume: 48,2%

By mass: 70,3%

Film Thickness 150-300 microns

Spreading Rate 2 – 7 square metres per litre.

Although the spreading rate will vary with porosity and type of substrate, for uncoated new surfaces work on 2-4 square metres per litre for the first coat and 5-7 square metres per litre for subsequent coats and when applied to sealed, previously painted substrates.

APPLICATION DETAILS

- Always stir well before use with a flat paddle.
- Application Method Suitable for machine application as well as with a paint roller or brush.
- Thinning Heritage Paints Roadmarking is ready for use un-thinned; thinning with Thinners/Toluene or Xylene will reduce its efficacy/hiding power.
- Only in case of machine application, thin with Thinners/Toluene or Xylene and clean with the same.
- One coat of Heritage Paints Roadmarking is used for best results.
- With brush, roller or spray, apply a generous coat of Heritage Paints Roadmarking.
- Only apply in well ventilated areas.
- This material is highly flammable. Keep away from all ignition sources, flames and sparks.
- Do not eat, drink or smoke while applying.
- Do not apply before 09:00 and after 16:00 in the winter.
- Do not apply exterior if it looks like rain will occur within 4-6 hours of application.

SURFACE PREPARATION

Substrate must be completely dry and free of dust. Remove all dust, foreign material, fungal and algae growth. Fill and seal all visible cracks with a suitable flexible sealant. Remove any old flaking paint coatings. Apply one coat of Heritage Paints Roadmarking to cover substrate well. For use on concrete, two applications are recommended. No primer is required.

COLOUR RANGE AND QUANTITIES

- Heritage Paints Roadmarking is available in White, Yellow, Red and Black.
- Available in 1 litre, 5 litres, 20 litres and 200 litres.

PRECAUTIONS

- Heritage Paints Roadmarking is highly flammable.
- Keep away from all ignition sources, flames and sparks. And only apply in well ventilated areas.
- Avoid inhaling vapours. Constant inhaling of vapours can lead to drowsiness. Expose person to fresh air and symptoms will disappear.
- Do not eat, drink or smoke while applying.



LEAVE A LASTING IMPRESSION



info@heritagepaints.co.za

www.heritagepaints.co.za | 0800 0 PAINT - 0800 0 72468

Heritage Paints C.C. 18 Garland Street, Ophirton, Johannesburg