

PRODUCT DESCRIPTION

New generation Pure Acrylic water based Low sheen abrasion resistant Floor Coating.

PRODUCT FEATURES

- Highly durable and UV resistant for the Harsh Gauteng climate.
- Highly water resistance.
- Excellent adhesion/abrasion resistance.
- Excellent, no mess application properties.
- Quick drying 2 coats can be applied in one day.
- Low odour.

APPLICATION AREAS

- Cement Paving tiles (new /weathered), (new/weathered), plaster, previously painted substrates.
- Primed metal and wooden substrates.

SURFACE PREPARATION

Uncoated cement tile surfaces: Remove all dust, foreign material, Fungal, algae growth-If oil is present clean/degrease with Heritage Brush Cleaner degreaser until the surface is water break free. (i.e. Free of oil)

Previously Painted Surfaces: Remove all loose, flaking and bubbling paint. Remove all dust, foreign material, Fungus and Algae growth. Allow to dry. If then powdery or friable seal with Heritage Bonding Liquid.

APPLICATION PROCEDURE

- Stir well before use.
- Brush, roller apply a generous coat of Heritage Floor Coating to the area, which needs protecting.
- Allow to dry 4-6 hours before recoating.
- Brush, roller or airless spray apply a second generous coat.

GENERAL

- Do not apply before 9am and after 4 pm in the Winter.
- Do not apply exterior if it looks like rain will occur with in 4-6 hours of application.
- Heritage Floor Coating is ready for use un-thinned, thinning with water will reduce its hiding power.
- Two coats of Heritage Floor Coating are used for best results.
- Although the spreading rate will vary with porosity and type of substrate. For uncoated new work on 6-8 SQM/l for the first coat and 8-10sqm/l for subsequent coats and for when applied to sealed, previously painted substrates.
- Application equipment clean up is with clean tap water.

COLOUR RANGE AND QUANTITIES

- Heritage Flor Coating is available in Red/black
- 1/5/20litres

PRECAUTIONS

- Heritage Floor Coating is not flammable,
- Contains no toxic substances and only low levels of VOC (EU regulations)



LEAVE A LASTING IMPRESSION



info@heritagepaints.co.za

www.heritagepaints.co.za | 0800 0 PAINT - 0800 0 72468

Heritage Paints C.C.18 Garland Street, Ophirton, Johannesburg