

PRODUCT DESCRIPTION

New generation Pure Acrylic water based Low sheen long life Roof Coating.

PRODUCT FEATURES

- Highly durable and UV resistant for the Harsh Gauteng climate.
- Highly water resistance.
- Excellent adhesion.
- Excellent, no mess application properties.
- Quick drying 2 coats can be applied in one day.
- Low odour.
- If correctly applied to a properly prepared substrate the product has a life expectancy of 5-7 years, possibly longer.

APPLICATION AREAS

- Cement tiles (new /weathered), Fibre cement sheeting (new/weathered), plaster, previously painted substrates.
- Primed metal and wooden substrates.

SURFACE PREPARATION

Rusted Metal: Affected areas need to be cleaned back to bright metal and spot primed with Heritage Water based Red Oxide metal primer.

New Metal: Surfaces need to be cleaned (Heritage Galvanized Iron Cleaner) to remove the manufacturer's grease protective layer this process is repeated until the surface is water break free. After drying the whole substrate is coated with Heritage Water based Red Oxide metal primer.

Uncoated cement tile surfaces: Remove all dust, foreign material, Fungal, algae growth- fill and seal all visible cracks and sealed with Heritage bonding liquid.

Uncoated weathered or new fibre cement surfaces: Remove dust, foreign material, Fungal, Algae growth and if friable, powdery seal with Heritage bonding liquid.

Previously Painted Surfaces: Remove all loose, flaking and bubbling paint. Remove all dust, foreign material, Fungus and Algae growth. Allow to dry. If then powdery or friable seal with Heritage bonding liquid.

APPLICATION PROCEDURE

- Stir well before use.
- Brush, roller or airless spray apply a generous coat of Heritage Roof Acrylic to the area, which needs protecting.
- Allow to dry 4-6 hours before recoating.
- Brush, roller or airless spray apply a second generous coat.

GENERAL

- Do not apply before 9am and after 4 pm in the Winter.
- Do not apply exterior if it looks like rain will occur with in 4-6 hours of application.
- Heritage Roof Acrylic is ready for use un-thinned, thinning with water will reduce its hiding power.
- Two coats of Heritage Roof Acrylic are used for best results.
- Although the spreading rate will vary with porosity and type of substrate. For uncoated new work on 6-8 SQM/l for the first coat and 8-10sqm/l for subsequent coats and for when applied to sealed, previously painted substrates.
- Application equipment clean up is with clean tap water.

COLOUR RANGE AND QUANTITIES

- Heritage Roof Acrylic is available in a range of popular none fade and UV resistant ready mixed Standard and Brighter colours
- 1/5/20 litres

PRECAUTIONS

- Heritage Acrylic Roof is not flammable,
- Contains no toxic substances and only low levels of VOC (EU regulations)



LEAVE A LASTING IMPRESSION



info@heritagepaints.co.za

www.heritagepaints.co.za | 0800 0 PAINT - 0800 0 72468

Heritage Paints C.C. 18 Garland Street, Ophirton, Johannesburg