



HERITAGE® P A I N T S

TECHNICAL DATA SHEET WATER BASED FIBROUS WATERPROOFING

PRODUCT DESCRIPTION

New generation water based pure acrylic Waterproofing compound, in which the re-enforcing Fibre membrane is incorporated into the ready to use liquid coating to provide a long lasting, seamless and flexible water proof coating for all roof types, parapet walls and other areas as required.

PRODUCT FEATURES

- Highly durable and UV resistant for the Harsh South African climate.
- Highly water resistant-with a low water up take -this coating won't let the water re-enter the areas it protects.
- Excellent adhesion and flexibility-this coating will move with building as it expands and contracts as the temperature fluctuates between night and day and Winter and Summer.
- Resists Algae and Fungus growth.
- Low odour.
- No messing around with not easy to use geo-fabric membranes.



APPLICATION AREAS

- Tile and fibre cement (asbestos) roofs, including ridging and flashing areas.
- Metal roofs, including overlap, screw heads and flashing areas.
- Parapet walls.
- To help seal vertical and horizontal cracks in walls, which even after filling may have a tendency to re open with time.

SURFACE PREPARATION

Rusted Metal: Affected areas need to be cleaned back to bright metal and spot primed with Heritage Water Based Metal Primer.

New Metal: Surfaces need to be abrasively degreased (Heritage Galvanized Iron Cleaner) to remove the manufacturer's grease protective layer this process is repeated until the surface is water break free. After drying the whole substrate is coated with Heritage Water Based Metal Primer.

Uncoated concrete roofs: Remove all dust, foreign material, Fungal, algae growth. Fill and seal all visible cracks and coat with Heritage Bonding Liquid.

Uncoated weathered or new fibre cement roofs: Remove dust, foreign material, Fungal, Algae growth and if friable, powdery seal Heritage Bonding Liquid.

Raw Plaster: Remove all dust, foreign material, Fungal and Algae growth. Fill and seal all visible cracks and coat with Heritage Plaster Primer.

Previously Painted Surfaces: Remove all loose, flaking and bubbling paint. Remove all dust, foreign material, Fungus and Algae growth. Allow to dry, If then powdery or friable seal with Heritage Bonding Liquid.

APPLICATION PROCEDURE

- Brush apply a generous coat of Heritage Fibrous Water Proofing to the area, which needs protecting.
- Allow to dry 4-6 hours.
- Brush apply a second generous coat.
- Allow the system to dry for at least 24 hours preferably longer in cold or very humid weather
- Overcoat the entire area with a final full coat of the product, check that all joints and cracks are well sealed.

GENERAL

- Do not apply before 9am and after 4 pm in the Winter.
- Do not apply if it looks like rain will occur within 4-6 hours of application.
- This product is normally applied by brush.
- Three, preferably Four coats of the product are used.
- Application equipment clean up is with clean tap water.

COLOURS AND QUANTITIES

- Red/Black/Grey
- 1/5/20 litre

PRECAUTIONS

- The product is not Flammable and contains no toxic materials.

LEAVE A LASTING IMPRESSION



info@heritagepaints.co.za

www.heritagepaints.co.za | 0800 0 PAINT - 0800 0 72468

Heritage Paints C.C. 18 Garland Street, Ophirton, Johannesburg